

2Mp Full HD IR IP Bullet Camera



Main Features

- ⇒ 1/3" 2.0 Megapixel CMOS Imge Sensor
- ⇒ High-Performance DSP
- ⇒ H.264 Video Compression and JPEG Image Capture
- ⇒ Max 25fps@1080P Resolution
- ⇒ IR Range max upto 20M
- ⇒ Support Alarm I/O, RS485 and RS232
- ⇒ Supports PoE and IP66 Rating Vandal Proof
- ⇒ Max 32GB Micro SD Card for Local Storage
- ⇒ Dual Encoding Streams Supported

| Feature | Specification |
|-----------------------|---|
| Image Sensor | 1/3" 2.0 Megapixel CMOS |
| Minimum Illumination | 0.1LUX/F1.2 |
| Shutter Speed | Auto/Manual, 1/3~1/10000s |
| White Balance | Auto/Manual |
| Gain Control(AGC) | Auto/Manual |
| Lens | 3.3-12mm |
| S/N Ratio | More than 50 dB |
| Video Compression | H264/ JPEG/MJPEG |
| Video Output | 1 channel BNC(1.0Vp-p, 75Ω) |
| Resolution | 1080P(1920×1080) / SXGA (1280×1024)/1.3M(1280× 960) /720P(1280×720) / D1(704×576) / CIF(352×288) |
| Frame Rate | HD 25/30 fps, Full HD 30 fps |
| Snapshot | Fastest 1fps JPEG capture |
| ICR | Supported |
| Audio Input | 1 channel, 3.5mm JACK LINE IN |
| Audio Output | 1 channel, 3.5mm JACK SPEAK OUT |
| Audio Compression | G.711a / G.711u / PCM |
| Alarm IN | 2 Input |
| Alarm Out | 1 Input |
| Interface | RJ-45 (10/100Base-T), RS232 & RS485 |
| Protocol | HTTP,TCP/IP,ARP,IGMP ,ICMP,RTSP,RTP,UDP,RTCP,SMTP,FTP,DHCP,DNS,DDNS,PPPOE,UPNP,NTP,Bonjour,SNMP |
| Internet Browser | Internet Explorer (6.0+), Chrome, Firefox, Safari |
| IR | IR Range max upto 20 Mtrs |
| Micro SD | Max 32GB, local storage |
| Auto Iris | Supported |
| Operating Temperature | -10°C~+60°C, 10%~90% |
| Power Source | DC12V(AC24V optional), PoE |
| Power Consumption | Max 10W |
| Weatherproof Standard | IP66 |
| Regulatory | CE, FCC and RoHS |
| Dimension | φ104 mm × 306.7 mm |
| Weight | 1.25Kg |