

DH-NVS0404/0804/1604HF-A

4/8/16 Channel H.264 Network Video Server



Features

- > 4/8/16 channel video and audio inputs
- > H.264 video compression and JPEG image capture
- > Full channel@D1(4CIF) realtime encoding
- > 3D intelligent positioning with Dahua PTZ dome camera
- > 3G (Model -E/-C only), Wi-Fi (Model -W only), 2SATA, 1USB
- > Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS

DH-NVS0404/0804/1604HF-A


Technical Specifications

Model	DH-NVS0404HF-A	DH-NVS0804HF-A	DH-NVS1604HF-A
System			
Main Processor	Dual-core embedded processor		
Operating System	Embedded LINUX		
Video			
Input	4 channel, BNC	8 channel, BNC	16 channel, BNC
Output	1HDMI, 1VGA, 1TV, 1Spot BNC(1.0Vp-p, 75Ω)		
Standards	PAL(625Line, 50f/s), NTSC		
Audio			
Input	4 channel	8 channel	4 channel
Output	1 channel		
Two-way Talk	1 channel		
Display			
Resolution	1920×1080, 1280×1024, 1280×720, 1024×768, 800×600		
Display Split	1	1/4	1/4/16
Privacy Masking	4 rectangular zones (each camera)		
Recording			
Video/Audio Compression	H.264 / G.711		
Resolution	D1/CIF/QCIF/VGA/QVGA		
Record Rate	Mainstream	D1/BCIF/CIF/QCIF(1~25/30fps)	
	Extra stream	CIF/QCIF	
Digital Watermark	Support		
Video Detection & Alarm			
Trigger Events	Recording, PTZ, Tour, Snapshot, Alarm, Video Push, Email, FTP, Spot, Buzzer & Screen Tips		
Video Detection	Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank		
Alarm Input	4 channel	8 channel	16 channel
Relay Output	3 channel		
Playback & Backup			
Search Mode	Time/Date, Alarm, Motion Detection & Exact search (accurate to second)		
Playback Functions	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom		
Storage			
Internal HDD	2 SATA		
Backup Mode	USB Device / Network		
Network			
Ethernet	RJ-45 (10/100/1000M)		

DH-NVS0404/0804/1604HF-A

Wireless	3G	EVDO(CDMA1X)/WCDMA and other 3G network (model-E/-C only)
	Wi-Fi	802.11b/802311g (model -W only)
Network Functions		TCP/IP, PPPOE,DDNS, FTP, IP Filter, DNS, SMTP, NTP, DHCP
Auxiliary Interface		
USB	1 Port	
RS232	PC communication	
RS485	PTZ control	
General		
Power Supply	DC12V / 3A	
Power Consumption	20W (Exclude HDD)	
Working Environment	-10°C ~ +50°C / 10%~90% / 86kpa~106kpa	
Dimension(W×D×H)	440mm x 300mm x 42.1mm	
Weight	2.5Kg	

Connection



* Take NVS0404HF-A as an example

<http://www.asi.ind.in>

Dahua Technology Co., Ltd.

1187 BinAn Road, Binjiang District, Hangzhou, China

Tel: +86-571-87688883

Fax: +86-571-87688815

Email: overseas@dahuatech.com

www.dahuatech.com

*Design and specifications are subject to change without notice.

© 2012 Dahua Technology Co., Ltd.