

MC22PA2R

Standard IR Dome Camera



Key Features

- 1/3 " Color Image Sensor
- 420TV Lines
- 24 units of IR LEDs covering 25 meter Distance range
- 0.5 LUX/F1.2
- Automatic Gain Control
- Back Light Compensation
- Auto White Balance



Specifications:

Image Sensor	1/3 " Color Image Sensor	
Pixels	PAL:512 (H)x582(V)	
Resolution	420TV Lines	
Min. Illumination	0.5LUX	
S/N Ratio	>48dB(AGC OFF)	
Electronic Shutter	NTSC:1/60 ~1/100,000 sec	PAL: 1/50 ~1/100,000 sec
Lens	3.6mm	
Gamma	>0.45(AGC OFF)	
White Balance	Manual/ATW/Fixed/AWC	
Gain Control (AGC)	Selectable	
Back Light Comp.	Selectable	
Day & Night (ICR)	Auto/Color/B&W	
OSD	NO	
Camera Title	IR Dome Camera	
Sync. System	Internal Sync	
Video Output	1.0Vp-p/75ohm	
Power Supply	DC12V±10%	
Power Consumption	< 6W	
Dimensions	92(R)×75(H)mm	
Weight	0.26kg	
Operating Temp.	-10°C ~ 50°C/30%~80%RH	