



THE COMPLETE SURVEILLANCE SYSTEM

MINITRAX VANDAL-RESISTANT PAN-TILT-ZOOM DOME CAMERA

CPT-FTD355

This versatile, vandal-resistant PTZ dome camera is a miniature version of the popular full-size Fastrax model. This dome is the right choice for applications that require a small, yet rugged, keyboard-controllable camera.

The enclosure is made of cast aluminum with a sealed, weather-resistant, polycarbonate dome.

Four tours can be programmed with preset locations. Additional programmable user preferences include alarm, preset, and title.

The Capture combination of superior image quality, versatile design, and PTZ control make the Minitrax a remarkable option for demanding applications.



▶ 10X OPTICAL, 10X DIGITAL ZOOM

▶ 60 PRE-POSITIONS PROGRAMMABLE

▶ 63 CAMERA ADDRESSES

FEATURES

- ▶ 10X optical zoom; 10X digital zoom
- ▶ 60 programmable preset positions
- ▶ Up to 63 selectable camera addresses
- ▶ Four programmable tours with preset locations
- ▶ One alarm input (OFF/NC/NO) and two alarm state (momentary, timeout)
- ▶ Programmable user preferences including alarm, preset, title, etc.
- ▶ Built-in RS-485 receiver driver
- ▶ Four auto-scan patterns
- ▶ Auto white balance
- ▶ Clear bubble with black liner
- ▶ Optional wall/ceiling mounting bracket available: CPT-FTD/WCM
- ▶ 24 VAC or 12 VDC
- ▶ Three-year warranty






THE COMPLETE SURVEILLANCE SYSTEM

MINITRAX VANDAL-RESISTANT PAN-TILT-ZOOM DOME CAMERA

CPT-FTD355



The CPT-FTD/WCM is an optional wall/ceiling mount bracket that can be added to the 480V series of dome cameras to enhance the camera's viewpoint.



CPT-FTD355HK
Heater kit.

TECHNICAL SPECIFICATIONS

SENSOR

Image Device	1/4-inch Super-HAD color CCD
Horizontal Resolution	430 TV Lines
Picture Elements	768 (H) x 494 (V), NTSC
Minimum Illumination	1.5 lux
Video Output	1.0 Vp-p, 75 ohms, composite
Lens	3.15 to 31.5 mm
Sync System	Internal/external (line lock auto switching)
S/N Ratio	48 dB
Backlight	On/off Compensation
Iris Control	Auto/manual (F1.8 to F32)
Shutter Speed	Normal ~ 1/10,000 second
Focus Mode	Auto/manual

GENERAL

Power Requirement	12 VDC / 24 VAC
Power Consumption	10 watts
Operating Temperature	14° F to 104° F; -10° C to 40° C
Dimensions (H x D)	5 3/4 x 4 5/8 inches; 145 x 117.2 mm

Unit Weight	2.87 lbs; 1.3 kg
-------------	------------------

PAN-TILT-ZOOM

Pan Travel	0 to 359°
Pan Speed	Maximum 120 degrees per second
Scanning Speed	7 degrees per second
Tilt	0 to 90 degrees
Tilt Speed	Maximum 120 degrees per second
Zoom	10X optical; 10X digital
Preset	60 programmable positions
Auto Scanning	Up to four courses
Tour Presets	Course (one to four x 16)
Title	Title display (on/off)

CONNECTORS

Video	One BNC
Power	Two-wire
Communication	RS-422/485

ACCESSORIES

Mounting	Optional wall/ceiling mounting bracket available: CPT-FTD/WCM
Heating	Optional heater kit available: CPT-FTD355HK