

# KPC138DT

## 21 LEDs IR Camera



### ● FEATURES

- (1) High sensitivity in the dark environment, 0.05 Lux / F2.0, 0Lux (IR ON)
- (2) Day and night features for 24-hour surveillance
- (3) Excellent image quality
- (4) IR LED effective range reaches up to 15 meters
- (5) IP67 standard approved case

### ● SPECIFICATIONS\*

MODEL	KPC138DT
Pick up Element	1/3" color CCD image sensor
Number of Pixel	512(H) x 492(V) <NTSC> / 512(H) x 582(V) <PAL>
Resolution	Standard
Min. Illumination	0.05 Lux / F2.0, 0Lux (IR ON)
IR LED	21 units
Effective Range	Up to 15 Meters
S/N Ratio	More than 48dB (AGC off)
Electronic Shutter	1/60 (1/50) to 1/100,000 sec.
Lens	f3.6mm / F2.0
Lens Angle	92.6°
IRIS Mode	AES
White Balance	ATW
Video Output	1.0 Vp-p composite, 75Ω
Power Source (±10%)	DC12V
Current Consumption (±10%)	70mA (IR OFF), 260mA (IR ON)
Dimensions (mm)**	140.19(L) x 55.2(W) x 79.58(H)
IP Rating	IP67

\* The specifications are subject to change without notice.

\*\* Dimensional Tolerance: ± 5mm

## Good Sensitivity in Low Illumination

KPC13x Series



Conventional



## True Color

KPC13x Series



Conventional

